


SW Half Coupling



Class 3000	Size	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
	A	1 1/8	1 1/8	1 1/8	1 3/8	1 1/2	1 3/4	1 7/8	2	2 1/2	2 1/2	2 3/4	3
	B	3/4	7/8	1 1/16	1 1/4	1 1/2	1 13/16	2 1/4	2 1/2	3	3 5/8	4 5/16	5 1/2
	C	0.420	0.555	0.690	0.855	1.065	1.330	1.675	1.915	2.406	2.906	3.535	4.545
	D	7/16	7/16	7/16	1/2	9/16	5/8	11/16	3/4	7/8	7/8	1	1 1/8
	Wt	0.125	0.125	0.125	0.188	0.313	0.563	0.813	1.000	2.000	2.625	3.875	6.625
Class 6000	Size	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
	A	-	-	-	1 3/8	1 1/2	1 3/4	1 7/8	2	2 1/2	2 1/2	2 3/4	3
	B	-	-	-	1 1/2	1 3/4	2 1/4	2 1/2	3	3 5/8	4 1/4	5	6 1/4
	C	-	-	-	0.855	1.065	1.330	1.675	1.915	2.406	2.906	3.535	4.545
	D	-	-	-	1/2	9/16	5/8	11/16	3/4	7/8	7/8	1	1 1/8
	Wt	-	-	-	0.375	0.563	1.000	1.438	2.000	3.875	5.500	6.625	13.125
Class 9000	Size	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2			
	A	-	-	-	1 3/8	1 1/2	1 3/4	1 7/8	2	2 1/2			
	B	-	-	-	1 13/16	2	2 3/8	2 3/4	3 1/16	3 5/8			
	C	-	-	-	0.855	1.065	1.330	1.675	1.915	2.406			
	D	-	-	-	1/2	9/16	5/8	11/16	3/4	7/8			
	Wt	-	-	-	0.88	1.16	1.88	2.50	3.25	5.38			

Information in this catalog was compiled from industry sources that Tech Tubes & Fitting believes to be reliable. We, however, do not guarantee the accuracy of this data.

ALL DIMENSIONS IN INCHES